



SystemSupervisor Presets

Model 212CIM with 212Sub-W

Note: All sub woofer delay settings assume the sub woofer physical placement is on the same vertical plane as the main system. If the sub enclosure is physically behind or in front of the main system then the delay values given must be adjusted accordingly.

Note: All setting below are Post Router. The Pre Router settings are user definable.

	LF	HF
Gain	0dB	-9.5dB
Polarity	Norm	Norm
Eq1 Type	PEQ	PEQ
Level	-4.5dB	-3.0dB
Frequency	561Hz	2593Hz
Bandwidth	0.333Oct	0.333Oct
Eq2 Type	PEQ	PEQ
Level	+3.0	+4.5dB

Frequency	70Hz	7775Hz
Bandwidth	0.35Oct	0.89Oct

Eq3 Type	PEQ	PEQ
Level	0dB	-1.5dB
Frequency	561Hz	5339Hz
Bandwidth	0.35Oct	0.187Oct

Delay

Pre Crossover	0mSec	0mSec
Post Crossover	1.2mSec	1.1mSec

Crossover

LPF		
Frequency	1029Hz	OFF
Type	24dB L-R*	

HPF		
Frequency	102Hz	1029Hz
Type	24dB L-R	24dB L-R

Dynamics

Threshold	+6dBu	+2dBu
Comp Ratio	2:1	3:1
Attack	10mSec	2mSec
Release	200mSec	125mSec

* NOTE: L-R = Linkwitz-Riley

SUB CHANNEL

Gain	+3dB
Polarity	Norm

Eq1

Type	PEQ
Level	+3.0dB
Frequency	54.1Hz
Bandwidth	0.5 Oct

Delay

Pre Crossover	0mSec
Post Crossover	0mSec

Crossover

HPF	
Frequency	35.1Hz
Type	24dB Butterworth

LFP	
Frequency	102Hz
Type	24dB L-R

Dynamics

Threshold	+6dBu
Comp Ratio	2:1
Attack	10.0mSec
Release	200mSec



ONE SYSTEMS®

One Systems USA, Inc. * 6204 Gardendale Dr. * Nashville, TN 37215

One Systems Group Co. Ltd. * European Division * Mittelsmoorer Strasse 12 * 28879 Grassberg German

One Systems Global Co., Ltd. * 87/114 Modern Town 15th Floor * Sukhumvit 63, Ekkamai Soi 3, Klongtoey, Bangkok, 1010 Thailand